

RIM-U

Flujo: Variable
 Max H: Variable
 Descarga: 3/8" ó 1/2"
 Voltaje: 115V / 230V

Características:

- Motor de Polo Sombreado
1/25 HP

No. de Parte	Modelo	Voltaje	Switch	Cable
545600	RIM-U	115V/230V		3'



Performance

Impeller Diameter	Discharge Adaptor (I.D. Tubing Size)	Flow - Gallons/Liters per hour	
		2 Ft / .6m	
		GPH	LPH
1.75" / 44.5 mm	1/2" / 12.7mm	290	1097
	5/8" / 15.8mm	435	1646
	3/4" / 19.1mm	540	2044
	1" / 24.5mm	585	2214
1.83" / 46.5 mm	1/2" / 12.7mm	360	1362
	5/8" / 15.8mm	550	2081
	3/4" / 19.1mm	700	2649
	1" / 24.5mm	810	3066
1.95" / 49.5 mm	1/2" / 12.7mm	385	1457
	5/8" / 15.8mm	600	2271
	3/4" / 19.1mm	760	2876
	1" / 24.5mm	825	3122
2.10" / 53.3 mm	1/2" / 12.7mm	400	1514
	5/8" / 15.8mm	600	2271
	3/4" / 19.1mm	700	2649
	1" / 24.5mm	760	2876